

Express Mailing

1 No. EL 813 876 291 US

PATENT APPLICATION  
Docket No. 14794.3.1

**UNITED STATES PATENT APPLICATION**

of

**KEVIN E. COLLIER**

for

**METHODS FOR CENTRIFUGALLY SEPARATING  
MIXED COMPONENTS OF A FLUID STREAM**

**WORKMAN, NYDEGGER & SEELEY**  
A PROFESSIONAL CORPORATION  
ATTORNEYS AT LAW  
1000 EAGLE GATE TOWER  
60 EAST SOUTH TEMPLE  
SALT LAKE CITY, UTAH 84111

20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100 101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000 1001 1002 1003 1004 1005 1006 1007 1008 1009 1010 1011 1012 1013 1014 1015 1016 1017 1018 1019 1020 1021 1022 1023 1024 1025 1026 1027 1028 1029 1030 1031 1032 1033 1034 1035 1036 1037 1038 1039 1040 1041 1042 1043 1044 1045 1046 1047 1048 1049 1050 1051 1052 1053 1054 1055 1056 1057 1058 1059 1060 1061 1062 1063 1064 1065 1066 1067 1068 1069 1070 1071 1072 1073 1074 1075 1076 1077 1078 1079 1080 1081 1082 1083 1084 1085 1086 1087 1088 1089 1090 1091 1092 1093 1094 1095 1096 1097 1098 1099 1100 1101 1102 1103 1104 1105 1106 1107 1108 1109 1110 1111 1112 1113 1114 1115 1116 1117 1118 1119 1120 1121 1122 1123 1124 1125 1126 1127 1128 1129 1130 1131 1132 1133 1134 1135 1136 1137 1138 1139 1140 1141 1142 1143 1144 1145 1146 1147 1148 1149 1150 1151 1152 1153 1154 1155 1156 1157 1158 1159 1160 1161 1162 1163 1164 1165 1166 1167 1168 1169 1170 1171 1172 1173 1174 1175 1176 1177 1178 1179 1180 1181 1182 1183 1184 1185 1186 1187 1188 1189 1190 1191 1192 1193 1194 1195 1196 1197 1198 1199 1200 1201 1202 1203 1204 1205 1206 1207 1208 1209 1210 1211 1212 1213 1214 1215 1216 1217 1218 1219 1220 1221 1222 1223 1224 1225 1226 1227 1228 1229 1230 1231 1232 1233 1234 1235 1236 1237 1238 1239 1240 1241 1242 1243 1244 1245 1246 1247 1248 1249 1250 1251 1252 1253 1254 1255 1256 1257 1258 1259 1260 1261 1262 1263 1264 1265 1266 1267 1268 1269 1270 1271 1272 1273 1274 1275 1276 1277 1278 1279 1280 1281 1282 1283 1284 1285 1286 1287 1288 1289 1290 1291 1292 1293 1294 1295 1296 1297 1298 1299 1300 1301 1302 1303 1304 1305 1306 1307 1308 1309 1310 1311 1312 1313 1314 1315 1316 1317 1318 1319 1320 1321 1322 1323 1324 1325 1326 1327 1328 1329 1330 1331 1332 1333 1334 1335 1336 1337 1338 1339 1340 1341 1342 1343 1344 1345 1346 1347 1348 1349 1350 1351 1352 1353 1354 1355 1356 1357 1358 1359 1360 1361 1362 1363 1364 1365 1366 1367 1368 1369 1370 1371 1372 1373 1374 1375 1376 1377 1378 1379 1380 1381 1382 1383 1384 1385 1386 1387 1388 1389 1390 1391 1392 1393 1394 1395 1396 1397 1398 1399 1400 1401 1402 1403 1404 1405 1406 1407 1408 1409 1410 1411 1412 1413 1414 1415 1416 1417 1418 1419 1420 1421 1422 1423 1424 1425 1426 1427 1428 1429 1430 1431 1432 1433 1434 1435 1436 1437 1438 1439 1440 1441 1442 1443 1444 1445 1446 1447 1448 1449 1450 1451 1452 1453 1454 1455 1456 1457 1458 1459 1460 1461 1462 1463 1464 1465 1466 1467 1468 1469 1470 1471 1472 1473 1474 1475 1476 1477 1478 1479 1480 1481 1482 1483 1484 1485 1486 1487 1488 1489 1490 1491 1492 1493 1494 1495 1496 1497 1498 1499 1500 1501 1502 1503 1504 1505 1506 1507 1508 1509 1510 1511 1512 1513 1514 1515 1516 1517 1518 1519 1520 1521 1522 1523 1524 1525 1526 1527 1528 1529 1530 1531 1532 1533 1534 1535 1536 1537 1538 1539 1540 1541 1542 1543 1544 1545 1546 1547 1548 1549 1550 1551 1552 1553 1554 1555 1556 1557 1558 1559 1560 1561 1562 1563 1564 1565 1566 1567 1568 1569 1570 1571 1572 1573 1574 1575 1576 1577 1578 1579 1580 1581 1582 1583 1584 1585 1586 1587 1588 1589 1590 1591 1592 1593 1594 1595 1596 1597 1598 1599 1600 1601 1602 1603 1604 1605 1606 1607 1608 1609 1610 1611 1612 1613 1614 1615 1616 1617 1618 1619 1620 1621 1622 1623 1624 1625 1626 1627 1628 1629 1630 1631 1632 1633 1634 1635 1636 1637 1638 1639 1640 1641 1642 1643 1644 1645 1646 1647 1648 1649 1650 1651 1652 1653 1654 1655 1656 1657 1658 1659 1660 1661 1662 1663 1664 1665 1666 1667 1668 1669 1670 1671 1672 1673 1674 1675 1676 1677 1678 1679 1680 1681 1682 1683 1684 1685 1686 1687 1688 1689 1690 1691 1692 1693 1694 1695 1696 1697 1698 1699 1700 1701 1702 1703 1704 1705 1706 1707 1708 1709 1710 1711 1712 1713 1714 1715 1716 1717 1718 1719 1720 1721 1722 1723 1724 1725 1726 1727 1728 1729 1730 1731 1732 1733 1734 1735 1736 1737 1738 1739 1740 1741 1742 1743 1744 1745 1746 1747 1748 1749 1750 1751 1752 1753 1754 1755 1756 1757 1758 1759 1760 1761 1762 1763 1764 1765 1766 1767 1768 1769 1770 1771 1772 1773 1774 1775 1776 1777 1778 1779 1780 1781 1782 1783 1784 1785 1786 1787 1788 1789 1790 1791 1792 1793 1794 1795 1796 1797 1798 1799 1800 1801 1802 1803 1804 1805 1806 1807 1808 1809 1810 1811 1812 1813 1814 1815 1816 1817 1818 1819 1820 1821 1822 1823 1824 1825 1826 1827 1828 1829 1830 1831 1832 1833 1834 1835 1836 1837 1838 1839 1840 1841 1842 1843 1844 1845 1846 1847 1848 1849 1850 1851 1852 1853 1854 1855 1856 1857 1858 1859 1860 1861 1862 1863 1864 1865 1866 1867 1868 1869 1870 1871 1872 1873 1874 1875 1876 1877 1878 1879 1880 1881 1882 1883 1884 1885 1886 1887 1888 1889 1890 1891 1892 1893 1894 1895 1896 1897 1898 1899 1900 1901 1902 1903 1904 1905 1906 1907 1908 1909 1910 1911 1912 1913 1914 1915 1916 1917 1918 1919 1920 1921 1922 1923 1924 1925 1926 1927 1928 1929 1930 1931 1932 1933 1934 1935 1936 1937 1938 1939 1940 1941 1942 1943 1944 1945 1946 1947 1948 1949 1950 1951 1952 1953 1954 1955 1956 1957 1958 1959 1960 1961 1962 1963 1964 1965 1966 1967 1968 1969 1970 1971 1972 1973 1974 1975 1976 1977 1978 1979 1980 1981 1982 1983 1984 1985 1986 1987 1988 1989 1990 1991 1992 1993 1994 1995 1996 1997 1998 1999 2000 2001 2002 2003 2004 2005 2006 2007 2008 2009 2010 2011 2012 2013 2014 2015 2016 2017 2018 2019 2020 2021 2022 2023 2024 2025 2026 2027 2028 2029 2030 2031 2032 2033 2034 2035 2036 2037 2038 2039 2040 2041 2042 2043 2044 2045 2046 2047 2048 2049 2050 2051 2052 2053 2054 2055 2056 2057 2058 2059 2060 2061 2062 2063 2064 2065 2066 2067 2068 2069 2070 2071 2072 2073 2074 2075 2076 2077 2078 2079 2080 2081 2082 2083 2084 2085 2086 2087 2088 2089 2090 2091 2092 2093 2094 2095 2096 2097 2098 2099 2100 2101 2102 2103 2104 2105 2106 2107 2108 2109 2110 2111 2112 2113 2114 2115 2116 2117 2118 2119 2120 2121 2122 2123 2124 2125 2126 2127 2128 2129 2130 2131 2132 2133 2134 2135 2136 2137 2138 2139 2140 2141 2142 2143 2144 2145 2146 2147 2148 2149 2150 2151 2152 2153 2154 2155 2156 2157 2158 2159 2160 2161 2162 2163 2164 2165 2166 2167 2168 2169 2170 2171 2172 2173 2174 2175 2176 2177 2178 2179 2180 2181 2182 2183 2184 2185 2186 2187 2188 2189 2190 2191 2192 2193 2194 2195 2196 2197 2198 2199 2200 2201 2202 2203 2204 2205 2206 2207 2208 2209 2210 2211 2212 2213 2214 2215 2216 2217 2218 2219 2220 2221 2222 2223 2224 2225 2226 2227 2228 2229 2230 2231 2232 2233 2234 2235 2236 2237 2238 2239 2240 2241 2242 2243 2244 2245 2246 2247 2248 2249 2250 2251 2252 2253 2254 2255 2256 2257 2258 2259 2260 2261 2262 2263 2264 2265 2266 2267 2268 2269 2270 2271 2272 2273 2274 2275 2276 2277 2278 2279 2280 2281 2282 2283 2284 2285 2286 2287 2288 2289 2290 2291 2292 2293 2294 2295 2296 2297 2298 2299 2300 2301 2302 2303 2304 2305 2306 2307 2308 2309 2310 2311 2312 2313 2314 2315 2316 2317 2318 2319 2320 2321 2322 2323 2324 2325 2326 2327 2328 2329 2330 2331 2332 2333 2334 2335 2336 2337 2338 2339 2340 2341 2342 2343 2344 2345 2346 2347 2348 2349 2350 2351 2352 2353 2354 2355 2356 2357 2358 2359 2360 2361 2362 2363 2364 2365 2366 2367 2368 2369 2370 2371 2372 2373 2374 2375 2376 2377 2378 2379 2380 2381 2382 2383 2384 2385 2386 2387 2388 2389 2390 2391 2392 2393 2394 2395 2396 2397 2398 2399 2400 2401 2402 2403 2404 2405 2406 2407 2408 2409 2410 2411 2412 2413 2414 2415 2416 2417 2418 2419 2420 2421 2422 2423 2424 2425 2426 2427 2428 2429 2430 2431 2432 2433 2434 2435 2436 2437 2438 2439 2440 2441 2442 2443 2444 2445 2446 2447 2448 2449 2450 2451 2452 2453 2454 2455 2456 2457 2458 2459 2460 2461 2462 2463 2464 2465 2466 2467 2468 2469 2470 2471 2472 2473 2474 2475 2476 2477 2478 2479 2480 2481 2482 2483 2484 2485 2486 2487 2488 2489 2490 2491 2492 2493 2494 2495 2496 2497 2498 2499 2500 2501 2502 2503 2504 2505 2506 2507 2508 2509 2510 2511 2512 2513 2514 2515 2516 2517 2518 2519 2520 2521 2522 2523 2524 2525 2526 2527 2528 2529 2530 2531 2532 2533 2534 2535 2536 2537 2538 2539 2540 2541 2542 2543 2544 2545 2546 2547 2548 2549 2550 2551 2552 2553 2554 2555 2556 2557 2558 2559 2560 2561 2562 2563 2564 2565 2566 2567 2568 2569 2570 2571 2572 2573 2574 2575 2576 2577 2578 2579 2580 2581 2582 2583 2584 2585 2586 2587 2588 2589 2590 2591 2592 2593 2594 2595 2596 2597 2598 2599 2600 2601 2602 2603 2604 2605 2606 2607 2608 2609 2610 2611 2612

# METHODS FOR CENTRIFUGALLY SEPARATING MIXED COMPONENTS OF A FLUID STREAM

## CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application is a continuation-in-part of U.S. Patent Application Serial No. 09/441,598, entitled CENTRIFUGAL PRESSURIZED SEPARATORS AND METHODS OF CONTROLLING SAME, filed November 17, 1999, which claims priority to provisional Application Serial No. 60/147,669, filed August 6, 1999.

## BACKGROUND OF THE INVENTION

### 1. The Field of the Invention

[0002] The present invention relates to methods for centrifugally separating components of fluids having different density.

### 2. The Relevant Technology

[0003] Water purification is an age-old activity that has been pursued to achieve both potable water and water for industrial use. With the rise of industrialization, water purification took on a new importance because industrial water usage generally involved discharging contaminated water into the environment. As concerns about the environment have increased, water discharged into the environment has been subjected to increasingly higher standards. Thus, increased efforts have been undertaken to identify methods of processing water to substantially reduce both dissolved and particulate pollutants.

[0004] One aspect of water purification that is particularly time consuming and/or equipment intensive is liquid-solid separation. Traditionally, settling ponds, or

WORKMAN, NYDEGGER & SEELEY  
A PROFESSIONAL CORPORATION  
ATTORNEYS AT LAW  
1000 EAGLE GATE TOWER  
60 EAST SOUTH TEMPLE  
SALT LAKE CITY, UTAH 84111



upsets the balance of the oil/water feed ratio to the separator. Although the separator may be controlled to prevent one component from entering the wrong exit stream, a catastrophic surge of one component or the other cannot be controlled.

CONFIDENTIAL

WORKMAN, NYDEGGER & SEELEY  
A PROFESSIONAL CORPORATION  
ATTORNEYS AT LAW  
1000 EAGLE GATE TOWER  
60 EAST SOUTH TEMPLE  
SALT LAKE CITY, UTAH 84111

## BRIEF DESCRIPTION OF THE DRAWINGS

[0008] Various embodiments of the present invention will now be discussed with reference to the appended drawings. It is appreciated that these drawings depict only typical embodiments of the invention and are therefore not to be considered limiting of its scope.

[0009] Figure 1 is a block diagram overview of a process that uses one or more of the separators of the present invention;

[0010] Figure 2 is a perspective view of one embodiment of a solid-liquid separator of the present invention;

[0011] Figure 3 is a cross-sectional view of one embodiment of the solid-liquid separator shown in Figure 2;

[0012] Figures 4A-B are cross-sectional views taken along line 4A-4A and 4B-4B of Figure 3, respectively;

[0013] Figure 5 is a perspective view of a partial assembly of the interior of the vessel of the solid-liquid separator shown in Figure 3, revealing a portion of the fin and disc assembly;

[0014] Figure 6 is a perspective view of a partial assembly of the interior of the vessel of the solid-liquid separator illustrated in Figure 3, revealing a more complete portion of the fin and disc assembly;

[0015] Figures 7A, B and C are alternative fin embodiments which may be utilized in the separators of the present invention;

[0016] Figure 8 is a perspective view of a partial assembly of the interior of the vessel of the solid-liquid separator illustrated in Figure 3, revealing a completed fin and disc assembly;

WORKMAN, NYDEGGER & SEELEY  
A PROFESSIONAL CORPORATION  
ATTORNEYS AT LAW  
1000 EAGLE GATE TOWER  
60 EAST SOUTH TEMPLE  
SALT LAKE CITY, UTAH 84111

[0017] Figure 9 is an elevational cross-sectional view taken along line 9-9 of Figure 3;

[0018] Figure 10 is a cross-sectional view of the solid-liquid separator illustrated in Figure 3 showing the solid-liquid separator in operation;

[0019] Figure 11 is a cross-sectional view of one embodiment of a liquid-liquid separator of the present invention;

[0020] Figure 12 is a perspective view of a partial assembly of the interior of the vessel of the liquid-liquid separator shown in Figure 11, revealing a portion of the fin and perforated disc assembly;

[0021] Figures 13A-13C are block diagrams showing alternative embodiments of valve assemblies controlling liquid flow into and out of the liquid-liquid separator;

[0022] Figure 14 is a block diagram showing another embodiment of a valve assembly controlling liquid flow into and out of the liquid-liquid separator;

[0023] Figure 15 is a block diagram overview of one process of the present invention that uses the liquid-liquid separator in connection with a hydrocyclone;

[0024] Figure 16 is a cross-sectional view of an alternative embodiment of a separator, wherein the spherical pressure vessel has been replaced with a double frusto-conical pressure vessel;

[0025] Figure 17 is a perspective view of a partial assembly of the interior of the vessel of the separator shown in Figure 16;

[0026] Figure 18 is an elevational side view of an alternative embodiment of a separator that can function as a solid-liquid and/or liquid-liquid separator;

[0027] Figure 19 is a cross sectional side view of the separator shown in Figure 18 without the supporting frame;

[0028] Figure 20 is a partially cutaway perspective view of a shaft assembly of the separator shown in Figure 19;

[0029] Figure 21 is a cross sectional side view of the separator taken along line 21-21 in Figure 19;

[0030] Figure 22 is an enlarged cross sectional view of the pressure vessel of the separator shown in Figure 19;

[0031] Figure 23 is a cross sectional side view of an extraction tube of the separator shown in Figure 22;

[0032] Figure 24 is a perspective view of a nozzle of the extraction tube shown in Figure 23;

[0033] Figure 25 is a plan view of a fin of the separator shown in Figure 22;

[0034] Figure 26 is a perspective view of a fin assembly of the separator shown in Figure 19;

[0035] Figure 27 is a cross sectional side view of an alternative embodiment of the extraction tube shown in Figure 24;

[0036] Figure 28 is a cross sectional side view of another alternative embodiment of the extraction tube shown in Figure 24; and

[0037] Figure 29 is a perspective view of a fin assembly of the separator shown in Figure 19 using solid discs.

## DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0038] The present invention relates to systems and corresponding apparatus for clarifying and/or separating components of a fluid stream. For example, in one embodiment, the system can be used for clarifying water or other liquids that have been contaminated with particulate matter, including organic and inorganic contaminants. The system can also be used for separating immiscible liquids such as an oil/water mixture or separating liquids of different density. Reference is now made to the drawings wherein like reference numbers refer to like unit operations or structures. The drawings are understood to be diagrammatic and/or schematic and are not necessarily drawn to scale nor are they to be limiting of the spirit and scope of the present invention.

[0039] Figure 1 is a block diagram overview of one embodiment of a system 8 that uses an inventive separator as a solid-liquid separator 10 and/or an oil-water separator 22. As illustrated in Figure 1, separators 10 and 22 are connected with a variety of other processing components. System 8 is configured for treatment of a fluid feed stream 12 that contains water, oil, and particulate. It is appreciated that depending on the content of feed stream 12 and the desired end components, select components of depicted system 8 can be removed, exchanged for other apparatus, or that additional components can be added.

[0040] Feed stream 12 may consist of a variety of different compositions, such as water which includes pollutants like oil, bacterial contaminants, dissolved metals and minerals, and colloidally suspended solids. Feed stream 12 may originate, by way of example and not by limitation, from industrial facilities, animal product processing facilities, sewage treatment, municipal water treatment, the petroleum industry, and any

WORKMAN, NYDEGGER & SEELEY  
A PROFESSIONAL CORPORATION  
ATTORNEYS AT LAW  
1000 EAGLE GATE TOWER  
60 EAST SOUTH TEMPLE  
SALT LAKE CITY, UTAH 84111



[illegible]

**WORKMAN, NYDEGGER & SEELEY**  
A PROFESSIONAL CORPORATION  
ATTORNEYS AT LAW  
1000 EAGLE GATE TOWER  
60 EAST SOUTH TEMPLE  
SALT LAKE CITY, UTAH 84111

**WORKMAN, NYDEGGER & SEELEY**  
A PROFESSIONAL CORPORATION  
ATTORNEYS AT LAW  
1000 EAGLE GATE TOWER  
60 EAST SOUTH TEMPLE  
SALT LAKE CITY, UTAH 84111

**WORKMAN, NYDEGGER & SEELEY**  
A PROFESSIONAL CORPORATION  
ATTORNEYS AT LAW  
1000 EAGLE GATE TOWER  
60 EAST SOUTH TEMPLE  
SALT LAKE CITY, UTAH 84111

flocculent. Such systems are available from Scott Powell Water Systems, Inc. of Denver, Colorado.

[0044] A coagulated effluent stream 34 supplies a development tank 36 that typically has a residence time of from about one to five minutes or longer. While in development tank 36, the particle size of the flocculent grows. Effluent stream 38 from development tank 36 supplies solid-liquid separator 10 which will be discussed below in greater detail. Solid-liquid separator 10 generates an particulate stream 40 constituting the particulate matter and gas that has been removed from the effluent stream 38, and an clarified stream 42 constituting the clarified water or other liquid. The clarified water in clarified stream 42 is discharged either directly or through a post filter 45 to the environment or other designed destination. Particulate stream 40 is supplied to filter 46 from which filter water stream 28 and a filter cake 48 are generated.

[0045] In one embodiment, gas and residual oil collected in the top of development tank 36 can be directly drawn off through line 49 to filter 46. It is also appreciated that oil-water separator 22, electrostatic coagulator 32, development tank 36, solid-liquid separator 10, and filter 46 can each be operated under an elevated pressure, such as by the application of a pump, so as to facilitate desired flows through the system. The pressure may vary in one or more of the components 22, 32, 36, 10 and 46 so as to control flow in desired directions.

[0046] Depicted in Figure 2 is one embodiment of solid-liquid separator 10 incorporating features of the present invention. Solid-liquid separator 10 includes a pressure vessel 60 which is driven by a motor 62. Although solid-liquid separator 10 of the present invention can be manufactured in a variety of different sizes, the depicted

WORKMAN, NYDEGGER & SEELEY  
A PROFESSIONAL CORPORATION  
ATTORNEYS AT LAW  
1000 EAGLE GATE TOWER  
60 EAST SOUTH TEMPLE  
SALT LAKE CITY, UTAH 84111

embodiment is designed to process approximately 40 liters/minute. In such an embodiment, a 2.5 horsepower, 3440 RPM electric motor can be utilized.

[0047] Pressure vessel 60 is preferably mounted within a guard 64. Guard 64 merely provides a shroud or housing as a safety mechanism to keep people and objects away from spinning pressure vessel 60. In the illustrated embodiment, a frame assembly 66 is provided to which guard 64 is mounted via mounting fins 68. One of skill in the art will, of course, appreciate that guard 64 may be configured and attached to frame assembly 66 in a variety of ways.

[0048] Frame assembly 66 is further configured to provide support to the motor 62 and the bearing structure which supports pressure vessel 60. Solid-liquid separator 10 includes a stationary inlet housing 70 configured to receive an inlet line 72. Similarly, a stationary outlet housing 74 is provided on the opposite end of the pressure vessel 60 to which is attached an outlet removal line 76 and an outlet effluent line 78.

[0049] A pump 80 is used to receive and feed effluent stream 38 to solid-liquid separator 10 through inlet line 72. Pump 80 pressurizes effluent stream 38 in inlet line 72 such that solid-liquid separator 10 operates under such pressure. Hence, pump 80 must be capable of pumping effluent stream 38 at the flow rate capacity of the solid-liquid separator 10 while maintaining a desired pressure. In one embodiment, pump 80 maintains effluent stream 38 at a pressure in a range between about 1 psi ( $6.89 \times 10^3$  Pa) to about 600 psi ( $4.14 \times 10^6$  Pa) with about 30 psi ( $2.07 \times 10^5$  Pa) to about 125 psi ( $8.61 \times 10^5$  Pa) being more preferred. Pump 80 also produces flow rates in a range between about 3 liters/minute to about 1,000 liters/minute. Any commercially available pump which can create the above pressures and the desired flow rates will function for

the desired purpose. Depending on the intended use, it is appreciated that the pressure range and flow rate can also be larger or smaller.

[0050] As illustrated in Figure 3, pressure vessel 60 is mounted for rotation about rotational axis 90 which also coincides with the rotational axis of solid-liquid separator 10. Pressure vessel 60 includes a peripheral wall 92 having an interior surface 93 bounding a chamber 95. In the embodiment depicted, chamber 95 is in the shape of a sphere, although other configurations may be utilized. Because vessel 60 is mounted for rotation about axis 90, pressure vessel 60 will generally include a geometry comprising a body of rotation about axis 90.

[0051] Additionally, it is desirable, although not required, that the walls of pressure vessel 60 slope radially outward towards an equator 97 having a maximum diameter that encircles rotational axis 90. Thus, although a pressure vessel with spherical walls 92 is one desired embodiment because of its efficient pressure bearing qualities, other curved-wall vessels, such as those having an oval, elliptical, or symmetrically irregular shape may be employed. Furthermore, straight-line configurations such as two truncated cones with their wide ends affixed together can be used. Similarly, a vessel having a cylindrical configuration at the edges and a center which is formed by truncated cones connected together can be used. In yet other embodiments, vessel 60 need not have outwardly sloping walls. For example, vessel 60 can be cylindrical or have a polygonal transverse cross section.

[0052] Pressure vessel 60 may be made out of a variety of materials including stainless steel, plastics, composites, filament wound structures, and other conventional materials. In one embodiment, pressure vessel 60 is capable of withstanding pressures in a range between about 1 psi ( $6.89 \times 10^3$  Pa) to about 2,000 psi ( $1.38 \times 10^7$  Pa) with

about 100 psi ( $6.89 \times 10^5$  Pa) to about 1,000 psi ( $6.89 \times 10^6$  Pa) being more preferred. In the embodiment depicted, pressure vessel 60 is made out of stainless steel and has two halves for ease of manufacture and construction. The two halves are secured together such as by welding, bolts, or other conventional methods such that a seam is formed at equator 97 of vessel 60.

[0053] As illustrated in Figure 3, solid-liquid separator 10 includes a drive shaft 94 at its inlet end 96 which is rigidly mounted to vessel 60. Drive shaft 94 is configured to engage motor 62 (Figure 2) as is known in the art. Drive shaft 94 is mounted within a hollow shaft 98 which is secured within inlet mounting collar 100. Inlet mounting collar 100, in turn, is secured to vessel 60 within a plurality of mounting bolts 102, in a manner known to one of skill in the art.

[0054] Drive shaft 94, hollow shaft 98, and inlet mounting collar 100 are thus all rigidly secured to each other and to vessel 60 by any of those methods known in the art, such as by welding or the use of bolts, such as mounting bolts 102 which engage an inlet mounting flange 104. These components comprise a drive assembly which is rigidly affixed to vessel 60 and, consequently, rotates with vessel 60.

[0055] The drive assembly is configured to engage inlet housing 70. Inlet housing 70 supports the drive assembly with an inlet bearing assembly 106 which, in this embodiment, engages the inlet mounting collar 100. Inlet bearing assembly 106 is a sealed ball bearing assembly resting in a pillow such as will be well known to one of skill in the art.

[0056] Inlet housing 70 is configured with a feed stream inlet 114 which is configured for receiving inlet line 72 (Figure 2) via any of those known attachment methods known in the art for providing fluid communication. As illustrated with

reference to Figures 3 and 4A, inlet housing 70 is further configured with an annular manifold cavity 108 which surrounds hollow shaft 98. Hollow shaft 98 includes a plurality of access ports 110. Mechanical pump seals 112 are provided between hollow shaft 98 and inlet housing 70 on each side of manifold cavity 108, thereby providing a fluid seal while allowing relative rotational movement between inlet stationary housing 70 and hollow shaft 98. Mechanical pump seals such as are available from A.W. Chesterton Co. of Stoneham, Massachusetts function for the desired purpose.

[0057] With continued reference to Figure 3, the support structure for vessel 60 at outlet end 120 is illustrated and described. As at inlet end 96, vessel 60 at outlet end 120 is similarly configured with an outlet mounting flange 122. An outlet mounting collar 124 is attached to outlet mounting flange 122 with a number of bolts 102. Outlet mounting collar 124 is supported on outlet housing 74 via an outlet bearing assembly 126.

[0058] Outlet housing 74 and outlet mounting collar 124 are each configured with a hollow interior for receiving an exit tube 128 having a removal channel 130 therein. As illustrated in Figure 4B, the hollow interior of outlet housing 74 and outlet mounting collar 124 is configured relative to exit tube 128 such that an annular effluent channel 132 is defined therebetween. Effluent channel 132 extends exterior of exit tube 128 and is in fluid communication with an effluent outlet 134 configured in outlet housing 74. Referring again to Figure 3, in one embodiment effluent outlet 134 includes a pressure relief valve 136 for maintaining pressure within vessel 60. Pressure relief valve 136 may be a one-way, spring-loaded fail shut valve in which the spring force must be overcome by a sufficient fluid pressure to force the valve open.

WORKMAN, NYDEGGER & SEELEY  
A PROFESSIONAL CORPORATION  
ATTORNEYS AT LAW  
1000 EAGLE GATE TOWER  
60 EAST SOUTH TEMPLE  
SALT LAKE CITY, UTAH 84111

[0059] An outlet end 129 of exit tube 128 is overfit with mechanical pump seal 138. The opposing end of mechanical pump seal 138 is rigidly affixed within a circular step configured in the interior end of outlet housing 74. Thus, mechanical pump seal 138 acts as a fluid barrier between removal channel 130 and effluent channel 132 and allows for relative rotational movement between exit tube 128 and outlet housing 74. The outlet end of outlet housing 74 is further configured with an exit orifice 140 which engages outlet removal line 76. Outlet removal line 76 is accessed through an exit valve 148 which may be a standard or solenoid valve, such as a ball valve that is commercially available.

Exit tube 128 also has an inlet end 131. In one embodiment, a plug 162 is received within the opening at inlet end 131. A gas escape orifice 164 extends through plug 162 so as to establish fluid communication between the center of chamber 95 and channel 130 extending through exit tube 128. Gas escape orifice 164 typically has a diameter in a range between about 0.02 inches (0.05 cm) to about 0.5 inches (1.3 cm) with about 0.02 inches (0.05 cm) to about 0.125 inches (0.3 cm) being more preferred. Depending on the intended use, this dimension can also be larger or smaller. In an alternative embodiment, inlet end 131 can simply be formed with a constricted orifice that communicates with removal channel 130, thereby precluding the need for plug 162.

[0060] With continued reference to Figure 3, exit tube 128 extends to the center of vessel 60. Solid-liquid separator 10 also includes a plurality of radially outwardly extending extraction tubes 160. Each extraction tube 160 has a first end 161 and an opposing second end 163. Each first end 161 is in fluid communication with exit tube 128 at inlet end 131 thereof. Extending through each extraction tube 160 is a channel having a diameter in a range from about 0.06 inches (0.15 cm) to about 2.0 inches (5

cm) with about 0.125 inches (0.3 cm) to about 0.5 inches (1.3 cm) being more preferred. In other embodiments the diameter can be smaller or larger. In one embodiment, eight extraction tubes 160 are employed, each spaced 45 degrees from the adjacent tube. In alternative embodiments, any number of extraction tubes 160 can be used. In one embodiment, a typical number of extraction tubes 160 ranges from about 2 to about 144 with about 4 to about 24 being more preferred.

[0061] In yet another embodiment, extraction tubes 160 need not radially outwardly project from exit tube 128 such that extraction tubes 160 are perpendicular to exit tube 128. Rather, extraction tubes 160 can outwardly project from exit tube 128 at an angled orientation. For example, in one embodiment, the inside angle between each extraction tube 160 and exit tube 128 may be in a range between about 90° to about 160°. In the embodiments where the inside angle is greater than 90°, exit tube 128 can be shorter so that inlet end 131 of exit tube 128 couples with first end 161 of each extraction tube 160. In yet other embodiments, the inside angle between each extraction tube 160 and exit tube 128 can be less than 90°.

[0062] Extraction tubes 160 each extend outwardly an equal distance from the rotational axis 90 of solid-liquid separator 10. Each extraction tube 160 has an opening 166 at its second end 163 for receiving separated particulate matter and fluid. In operation, extraction tubes 160, as further explained below, assist in defining a boundary line between the collected particulate matter and the clarified liquid. Thus, the length of extraction tubes 160 is set to provide a predetermined boundary line within vessel 60. In one embodiment in which vessel 60 has a maximum inner diameter of 19 inches at equator 97, extraction tubes 160 are configured to leave a 0.25 inch (0.65 cm) space between opening 166 in tubes 160 and wall 92 of vessel 60. In alternative



embodiments, including those of different sized vessels, the space between the opening 166 in extraction tubes 160 and wall 92 of vessel 60 is typically in a range between about 0.125 inches (0.3 cm) to about 2 inches (5 cm) with about 0.25 inches (0.6 cm) to about 1 inch (2.5 cm) being more preferred. In other embodiments, the space can be smaller or larger.

[0063] Vessel 60 is also configured with a plurality of fins and discs for channeling fluid flow through vessel 60. One embodiment of solid-liquid separator 10 includes a center disc 170, positioned in the center of vessel 60 and oriented perpendicular to rotational axis 90, as illustrated in Figure 3. Center disc 170 is configured with a central orifice which fits over plug 162. Center disc 170 extends in a circular configuration radially outward from plug 162. Outer edge 172 of disc 170 is circular (following the curvature of vessel 60) and is configured to provide an axial flow passage 174 between the edge 172 of disc 170 and wall 92 of vessel 60. Flow passage 174 extends annularly about axis 90. Outer edge 172 is typically, although not necessarily, disposed radially inward from opening 166 of extraction tubes 160. In one embodiment, the distance between edge 172 of disc 170 and wall 92 of vessel 60 is in a range between about 0.5 inches (1.3 cm) to about 4 inches (10 cm) with about 0.8 inches (2 cm) to about 1.2 inches (3 cm) being more preferred. In other embodiments, this distance can also be larger or smaller.

[0064] The depicted embodiment also includes four additional discs 176, 178, 202 and 204. Discs 176 and 202 are positioned on the inlet side of vessel 60 with discs 178 and 204 positioned on the outlet side. Discs 176, 178, 202 and 204 are used in part to facilitate assembly of the solid-liquid separator 10 and to provide structural support during operation thereof. Alternatively, the solid-liquid separator 10 can be assembled

with fewer or greater numbers of assembly discs. It is also envisioned that the inventive solid-liquid separator 10 can be constructed without discs by securing the fins, as discussed below, directly to exit tube 128 and/or wall 92 of vessel 60.

[0065] As illustrated in Figures 5 and 6, discs 176 and 202 include central orifices 180 which allow gas that collects at the center of the vessel 60 to be extracted. Discs 178 and 204 are similarly configured with central orifices 182 slightly larger than the outside diameter of exit tube 128, thereby accommodating passage therethrough of exit tube 128. V-notches 210 may be formed, such as by being laser cut, into outer edge 172 of disc 170. These v-notches minimize the disturbance of the collected particulate matter as the clarified water flows around disc 170. In one embodiment, these v-notches 210 are cut at the edge 172 of disc 170 having a width in a range between about 0.1 inch (0.25 cm) to about 1 inch (2.5 cm) and a depth in a range between about 0.1 inch (0.25 cm) to about 1 inch (2.5 cm). The number of v-notches 210 that are cut into center disc 170 between each pair of fins 184 is typically in a range between about three notches to about eight notches. Alternatively, the number and size of these v-notches 210 can be increased or reduced.

[0066] Referring now to Figure 5, solid-liquid separator 10 also includes a plurality of radial fins 184. Each fin 184 has an inside edge 186 which is generally parallel to rotational axis 90 and an outside edge 188 which generally follows the curvature of vessel 60. Thus, in the configuration illustrated herein, in which spherical vessel 60 is employed, outside edge 188 of fins 184 has a substantially semi-circular configuration.

[0067] In the embodiment illustrated in Figure 8, two types of fins 184 are used: trimmed fins 212 and untrimmed fins 214. As depicted in Figure 7A, each trimmed fin 212 includes a substantially flat inside edge 186 and an opposing outside edge 188.

Outside edge 188 includes a substantially flat side portion 187 orthogonally projecting from each end of inside edge 186, a centrally disposed substantially flat nose portion 189 disposed substantially parallel to inside edge 186, and a curved shoulder portion 191 extending from each side portion 187 to opposing ends of nose portion 189.

[0068] As illustrated in Figure 7B, each untrimmed fin 214 includes a substantially flat inside edge 186 and an opposing outside edge 188. Outside edge 188 includes a substantially flat side portion 187 orthogonally projecting from each end of inside edge 186 and a curved face portion 193 extending between each side portion 187. A centrally disposed semi-circular notch 194 is formed on face portion 193.

[0069] An alternative fin 215 is illustrated in Figure 7C. Fin 215 has substantially the same configuration as untrimmed fin 214 except that notch 194 is replaced with holes 196 extending through fin 215. Such holes 196 typically have a diameter in a range between about 0.5 inches (1.3 cm) to about 1.5 inches (3.8 cm).

[0070] Fins 184 are positioned within chamber 95 of vessel 60 perpendicularly to discs 170, 176, 178, 202 and 204 as best illustrated in Figures 5 and 6. Each disc is provided with a slot 198 which corresponds to each fin 184. Slots 200, which correspond to each disc 170, 176, 178, 202 and 204, are also configured in each fin 184. Fins 184 and discs 170, 176, 178, 202 and 204 are in one embodiment formed of stainless steel but can also be formed from plastics, composites, and other sufficiently strong material. Slots 198 and 200 may be formed using any conventional method such as by laser cutting. Slots 198 and 200 are configured to allow the fins and discs to engage each other in a slip fit, mating relationship. Thus, slots 198 configured in discs 170, 176, 178, 202 and 204 have a width at least as great as the thickness of fins 184.

Similarly, slots 200 configured in fins 184, have a width at least as great as the thickness of the discs 170, 176, 178, 202 and 204 which correspond to these slots.

[0071] The fin and disc assembly within vessel 60 is thus assembled as illustrated in Figure 5 by positioning outlet discs 204 and 178 over exit tube 128. Center disc 170 as seen in Figure 6 is then placed about plug 162 and some fins 184 are engaged into their corresponding slots on the discs 170 and 178 while simultaneously engaging the discs with the corresponding slots on fins 184. When fin 184 is thus placed into mating engagement with a disc, virtually all relative movement between the disc and the fin is prohibited. Inlet discs 176 and 202 are then placed into mating engagement with slots 200 on fins 184. With all five discs 170, 176, 178, 202 and 204 now in position, the remaining fins are installed by sliding them radially into position, until the interior configuration of the vessel 60 is complete as illustrated in Figure 8. Slots 198 and 200 are simply one way of securing the fins and discs together. In alternative embodiments, the fins and discs can be welded, clamped, integrally molded, or otherwise secured together using conventional methods.

[0072] In the depicted embodiment, twenty four fins 184 are utilized in vessel 60, as illustrated in Figures 8 and 9. In alternative embodiments, the number of fins 184 is typically in a range between about 8 to about 144 with about 12 to about 48 being more preferred. As best depicted in Figure 3, 8, and 9, the assembled fins 184 radially outwardly project from rotational axis 90 in substantially parallel alignment with rotational axis 90. Each inside edge 186 is spaced apart from the center of rotational axis 90 so that a channel 219, depicted in Figure 3, is formed that extends from inlet end 96 to gas escape orifice 164. Channel 219 has a diameter typically in a range between about 0.25 inches (0.6 cm) to about 2 inches (5 cm) with about 0.25 inches (0.6 cm) to

U.S. PATENT & TRADEMARK OFFICE

WORKMAN, NYDEGGER & SEELEY  
A PROFESSIONAL CORPORATION  
ATTORNEYS AT LAW  
1000 EAGLE GATE TOWER  
60 EAST SOUTH TEMPLE  
SALT LAKE CITY, UTAH 84111

about 1 inch (2.5 cm) being more preferred. Depending on the intended use, the diameter can also be smaller or larger. As illustrated in Figures 7A and 7B the inside edge 186 of each fin 184 is cut to prevent interference with exit tube 128 and gas escape plug 162.

[0073] To accommodate the eight radial extraction tubes 160, trimmed fins 212 are modified with a central notch 216 as illustrated in Figure 5. Notch 216 is sized to allow some degree of intersection of trimmed fins 212 with extraction tubes 160, as illustrated in Figure 9. Hence, in the depicted embodiment, sixteen trimmed fins 212 as modified with a notch 216 are utilized in combination with eight untrimmed fins 214 which have not been so modified.

[0074] In an alternative embodiment, it is appreciated that fins 184 need not radially outwardly project in alignment with rotational axis 90. Rather, inside edge 186 of each fin 184 can be offset from alignment rotational axis 90 and still be retained in position by the discs. As used in the specification and appended claims, the phrase, "fin projecting from toward the rotational axis" is broadly intended to include embodiments where an inside edge of a fin is disposed in a plane that is either aligned with or offset from the rotational axis, where at least a portion of the inside edge is directly disposed along the rotational axis or is radially spaced outward from the rotational axis, and/or where the inside edge is parallel with or angled relative to the rotational axis.

[0075] With the fins and discs assembled about exit tube 128 as illustrated in Figure 8, the internal assembly is enclosed within chamber 95 of vessel 60. In one embodiment, vessel 60 is comprised of two halves which are secured together, such as by welding or bolting with a seal such as a gasket or o-ring disposed therebetween. By covering the internal assembly of Figure 8 within wall 92 of vessel 60, the fins and

discs become locked to each other in relative engagement and no welding is needed to hold them secure.

[0076] Specifically, as depicted in Figure 10, flat side portions 187 of each fin 184 are disposed adjacent to mounting flanges 104 and 122. Curved shoulder portions 188 of trimmed fins 212 are disposed adjacent to wall 92. Similarly, curved face portion 193 of untrimmed fins 214 are also disposed adjacent to wall 92. Side portions 187, shoulder portions 188, and face portion 193 of fins 184 can be directly biased against vessel 60. Alternatively, a small gap, typically less than about 1/4 inch, can be formed between vessel 60 and portions 187, 188, and 193. As illustrated in Figure 9, the positioning of fins 184 adjacent to wall 92 results in the formation of a plurality of discrete flow channels 218 through vessel 60 along the rotational axis. Each flow channel 218, however, is partially blocked by the intersection of the various discs 170, 176, 178, 202, and 204. As a result of the discs, fluid traveling through flow channels 218 is required to flow around the outer edge of the discs.

[0077] Returning to Figure 10, an underflow passage 190 is formed between flat nose portion 189 of trimmed fins 214 and wall 92. Underflow passage 190 enables fluid to flow between discrete flow channels 218 at equator 97. In one embodiment, the maximum gap between flat nose portion 189 of trimmed fin 214 and wall 92 is in a range between about 0.125 inches (0.3 cm) to about 2 inches (5 cm) with about 0.25 inches (0.6 cm) to about 1 inch (2.5 cm) being more preferred. In other embodiments, the maximum gap can be larger or smaller. Although not required, in one embodiment flat nose portion 189 of each fin 184 is positioned radially inward from opening 166 of each corresponding extraction tube 160.

[0078] It is of course envisioned that fins 184 can be formed in a variety of different configurations to facilitate underflow passage 190 between flow channels 218. For example, trimmed fins 212 can be replaced with alternative fins 215. In this embodiment, holes 196 facilitate underflow passage 190. In yet other embodiments, notches, slots, holes, grooves, and the like can be formed in a fin 184 to facilitate underflow passage 190.

[0079] Notch 194 (Figure 7B) formed in untrimmed fins 214 is designed to perform two functions. First, in an embodiment where a seam is formed at equator 97, such as an inside flange, notch 194 provides space to receive the seam. Notch 194 also functions to allow at least some flow between flow channels 218 separated by untrimmed fins 214. Fluid flow through notch 194 thus helps to insure that boundary layers and flow rates are the same in each flow channel 218.

[0080] Once the internal assembly is enclosed within vessel 60, the inlet and outlet mounting collars 100, 124, the bearing assemblies, and housings assembled as described above are bolted or otherwise secured to vessel 60 using conventional methods known to those skill in the art.

[0081] In operation, as illustrated in Figure 2, rotation of the vessel 60 is commenced by turning on motor 62. Motor 62 typically causes vessel 60 to rotate with a rotational velocity in a range between about 600 rotations/minute to about 10,000 rotations/minute with about 1,200 rotations/minute to about 3,600 rotations/minute being more preferred. A stream 38 is received by pump 80 which pumps stream 38 into the solid-liquid separator 10 through inlet line 72. Stream 38 is preferably pressurized by pump 80 such that a hydraulic pressure is maintained within vessel 60 during operation of the solid-liquid separator 10. In one embodiment vessel 60 of solid-liquid

separator 10 operates under a hydraulic pressure in a range between about 1 psi ( $6.89 \times 10^3$  Pa) to about 600 psi ( $4.14 \times 10^6$  Pa) with about 30 psi ( $2.07 \times 10^5$  Pa) to about 125 psi ( $8.61 \times 10^5$  Pa) being more preferred. Depending on the intended use, the rotational velocity and operating pressure can be greater or smaller.

[0082] In addition to the hydraulic pressure applied to vessel 60 by stream 38, a centrifugal force is applied to stream 38 and vessel 60 as a result of the rotation of vessel 60. This centrifugal force increases as the distance away from rotational axis 90 increases. As such, the total force at the perimeter of vessel 60 may be several times that of the hydraulic pressure.

[0083] Stream 38 may include virtually any liquid which has been contaminated with a particulate component having a density greater than the liquid. For most applications, however, the liquid will be water. Thus, although water is referred to herein as the liquid being clarified, it will be understood that solid-liquid separator 10 of the present invention may be used to clarify a variety of liquids.

[0084] As illustrated in Figure 10, feed stream 38 enters the solid-liquid separator 10 through feed stream inlet 114. As feed stream 38 reaches the rotating hollow shaft 98, it is forced through access ports 110 (see also Figure 4) into the hollow shaft 98 where the stream is accelerated to the same rotational velocity as vessel 60. Flow through rotating hollow shaft 98 proceeds in the direction of arrow A. Upon reaching the entrance to vessel 60 adjacent inlet mounting flange 104, the centrifugal force imposed due to the rotation of vessel 60 pushes the stream radially outwardly towards wall 92 of vessel 60. As the stream enters vessel 60, it enters one of the flow channels 218 (Figure 9) and proceeds to fill vessel 60.



[illegible]

**WORKMAN, NYDEGGER & SEELEY**  
A PROFESSIONAL CORPORATION  
ATTORNEYS AT LAW  
1000 EAGLE GATE TOWER  
60 EAST SOUTH TEMPLE  
SALT LAKE CITY, UTAH 84111

**WORKMAN, NYDEGGER & SEELEY**  
A PROFESSIONAL CORPORATION  
ATTORNEYS AT LAW  
1000 EAGLE GATE TOWER  
60 EAST SOUTH TEMPLE  
SALT LAKE CITY, UTAH 84111

until boundary line 228 is located radially inward of opening 166 of extraction tubes 160 (a condition illustrated in Figure 10). Collected solids 224 are subsequently extracted from pressure vessel 60 through extraction tubes 160 as described below.

[0088] Water flowing around the edge of disc 170 through axial flow passage 174 can stir up collected solids 224 that have settled at the largest dimension radius or equator 97 of pressure vessel 60. Although not always, in one embodiment this stirring caused by eddy effects works in opposition to the purpose of solid-liquid separator 10. Therefore, notches such as v-notches 210 previously discussed with regard to Figure 6 may be cut in the outer perimeter of disc 170. The notches minimize stirring by reducing the force of the water flow around disc 170, thereby reducing the eddy effects. Thus the v-notches 210 maintain boundary layer 228 between collected solids 224 and clarified water 226.

[0089] Apart from functioning to support fins 184, the various discs, particularly disc 170, function to assist in the removal of the particulate matter. That is, all fluid that enters vessel 60 must flow either to or around the outer edge of disc 170 before it can exit vessel 60. By forcing all of the fluid to flow to the outer edge of disc 170 at equator 97, all of the fluid is subject to the greatest centrifugal force produced by the rotation of vessel 60, thereby ensuring that the highest concentration of particulate matter is removed from the incoming fluid. Discs 176 and 178 also function for this purpose. Furthermore, by positioning discs 176 and 178 on opposing sides of disc 170, the fluid flows radially inward and outward as it moves between the discs. This radial movement of the fluid increases the retention time of the fluid within the vessel, thereby subjecting the fluid to the centrifugal force of the vessel for a longer period of time. As a result, a larger portion of the particulate matter is removed. In an alternative embodiment,

however, the inventive solid-liquid separator can be operated without the use of the discs, particularly disc 170.

[0090] Because gases may occasionally be found in fed stream 38, a gas layer 230 may form about axis 90 on the inlet side of vessel 60. Disc 170 effectively serves as a barrier between the inlet side and the outlet side of vessel 60. Hence, gases found within the feed stream will generally be found only on the inlet side of vessel 60 because they are likely to be separated before the liquid passes through axial flow passage 174.

[0091] As feed stream 38 continues to flow into the vessel 60, the fluid passes around the outer perimeter of center disc 170 and into the outlet side of vessel 60. Clarified water 226, which can be other fluids in other embodiments, fills the outlet side of vessel 60 and then flows out through effluent channel 132. Clarified water 226 subsequently exits solid-liquid separator 10 through effluent outlet 134 and pressure relief valve 136. Pressure relief valve 136 only opens when the back pressure in effluent outlet 134 overcomes the spring force for the valve, thereby ensuring that a predetermined pressure is maintained inside vessel 60. In an alternative embodiment, pressure relief valve 136 can be replaced with other operating systems that perform the same function. For example, pressure relief valve 136 can be replaced with an electronically operated valve and a pressure sensor. The valve is electronically opened when the pressure sensor senses a predetermined pressure within vessel 60 or outlet 134. In other embodiments, valve 136 can be self-adjusting so as to allow clarified water 226 to continually flow therethrough at a given pressure. Should the flow increase or decrease, valve 136 automatically opens or closes a proportional amount so that the pressure is held substantially constant.

[0092] Boundary line 228 is maintained at a desired level by periodically opening valve 148 and allowing collected solids 224 to be extracted through extraction tubes 160. When valve 148 is opened, a pressure gradient is created between the interior of vessel 60 and outlet removal line 76. Flow of collected solids 224 proceeds from the higher pressure environment within vessel 60 to the lower pressure through extraction tubes 160. This pressure differential may be created a number of ways, such as by operating vessel 60 at ambient pressure and imposing a negative pressure on extraction tubes 160, or, as is presently depicted, operating vessel 60 under pressure and imposing extraction tubes 160 to a near ambient pressure.

[0093] Recognizing that the eight extraction tubes 160 only extend into eight of the flow channels 218 (Figure 9), boundary line 228 drops in these flow channels 218 as collected solids 224 are extracted. As boundary line 228 in these flow channels 218 drops, collected solids 224 from adjacent flow channels 218 flows through underflow passage 190 to maintain boundary line 228 at a generally constant level throughout the circumference of vessel 60. In an alternative embodiment, it is envisioned that an extraction tube 160 can be feed to each discrete flow channel 218. In this embodiment, it is not necessary to have underflow passage 190 between flow channels 218, *i.e.*, fins 184 can extend all the way to wall 92 of vessel 60 along the length of fins 184.

[0094] When exit valve 148 is opened, any gas which has built up inside vessel 60 to form a gas layer 230 will immediately begin escaping through orifice 164 of plug 162 which is in fluid communication with removal channel 130. Thus, orifice 164 should preferably be sized such that any anticipated gas buildup may be removed through the periodic opening of valve 148. Orifice 164, however, should be sufficiently small so as to enable sufficient draw on extraction tubes 160 to remove collected solids 224. Thus,

the size of orifice 164 depends in part upon the constituency and nature of the fluid flow. In one embodiment, orifice 164 has a threaded diameter of approximately 0.375 inch (1 cm). This 0.375 inch (1 cm) orifice is threaded to allow an insert whereby the orifice diameter may be reduced or even totally occluded, depending upon the insert selected. An insert may be threaded into orifice 164 even after construction of the pressure vessel 60 because orifice 164 remains accessible through exit orifice 140 and removal channel 130. The adjustable nature of this orifice diameter allows orifice 164 to be tailored for different fluid flows while using the same solid-liquid separator 10.

[0095] In one embodiment of the present invention, spherical vessel 60 has an inside diameter of about 19 inches (48 cm) and is capable of processing approximately 38 liters of water each minute. This provides a residence time of approximately 1.5 minutes in solid-liquid separator 10 while subjecting the water to an average of approximately 700 g forces. This is roughly the equivalent of 2 hours of residence time in a static clarifier having the same capacity. In one embodiment, the solid-liquid separator is capable of clarifying water to remove at least 99% of solids. In alternative embodiments, the present invention envisions that typical vessels can be formed having a maximum inside diameter in a range between about 6 inches (15 cm) to about 120 inches (300 cm) with about 12 inches (30 cm) to about 60 inches (150 cm) being more preferred. Such vessels can be designed to process fluid at a rate in a range from about 0 liters/minute to about 4,000 liters/minute with about 1 liter/minute to about 1,000 liters/minute being more preferred. It is appreciated that in other embodiments, the above variables can be larger or smaller.

[0096] The resulting particulate stream 40 is passed through a bag filter, filter press, and/or belt filter to remove remaining water and to "cake" the solids. The "caked"

solids may then be disposed of by composting or other method known in the art. Ultimately, the disposal method will depend upon the composition of the "caked" solids. For instance, solids containing heavy metals cannot be composted and other appropriate disposal methods will be used.

[0097] To shut down solid-liquid separator 10, the pump and motor are turned off, then vessel 60 is drained and flushed. Alternatively, fluid may simply be left within the vessel 60 during non-use.

[0098] In one embodiment, depending on the operating parameters and the particle matter being collected, collected solids 224 can be difficult to fully extract from vessel 60 through extraction tubes 160. For example, collected solids 224 can be caked on wall 92 to such an extent that they do not freely flow into extraction tubes 160. In one approach to more easily and fully removing collected solids 224, the inflow of stream 38 to vessel 60 and the outflow of clarified water 226 from vessel 60 can be momentarily stopped. While vessel 60 continues to rotate, a removal stream can be pumped into removal channel 130 of exit tube 128 so that the removal stream passes down through extraction tubes 160 and into vessel 60.

[0099] As the removal stream passes into vessel 60, the removal stream resuspends the caked solids into surrounding fluid. The centrifugal force, however, keeps the particulate matter substantially adjacent to perimeter wall 92. Once the particulate matter is resuspended in a less dense phase, extraction tubes 160 can return to their original operation where the fluid containing the resuspended particulate matter is drawn out of vessel 60 through extraction tubes 160 and exit tube 128. Once a desired amount of the particular matter is removed, flow through extraction tubes 160 can be closed while rotating vessel 60 resettles the particulate matter against peripheral wall

92. Once the particulate matter is sufficiently settled, feed stream 38 and clarified water can again flow into and out of vessel 60.

[00100] As will be discussed below in greater detail different forms of nozzles can be placed at then end of extraction tubes 160 for more efficiently resuspended the particulate matter. Furthermore, a separate tube can be used to deliver the removal stream into vessel 60.

[00101] Depicted in Figures 11 and 12, another embodiment of the present invention relates to a liquid-liquid separator 244 that uses a similar construction to solid-liquid separator 10 depicted in Figures 2-10. In contrast to solid-liquid separator 10 that is primarily designed to remove particulate from a fluid, liquid-liquid separator 244 is primarily designed to separate a mixed liquid of two or more immiscible liquids such as oil and water or any other types of immiscible liquids. Liquid-liquid separator 224 can thus be used as oil-water separator 22.

[00102] Figure 12 illustrate a subassembly 232 of liquid-liquid separator 244. Subassembly 232 includes a solid inlet side minor disk 234 similar to inlet side minor disk 176 depicted in Figure 6. A center disk 236 is depicted as having a plurality of perforations 238. Perforations 238 allow for the passage of the liquids therethrough. Additionally, an outlet side minor disk 240 is also depicted as having a plurality of perforations 238 extending therethrough.

[00103] As depicted in Figure 11, the remainder of subassembly 232 and the vessel in which subassembly 232 is disposed are substantially the same as that previously discussed with regard to solid-liquid separator 10. As such, like elements are identified by like reference characters. Furthermore, the alternatives discussed above with regard to solid-liquid separator 10 are also applicable to liquid-liquid separator 244.

[00104] Liquid-liquid separator 244 also operates in a manner similar to solid-liquid separator 10. For example, with vessel 60 rotating, the mixed liquid is pumped into inlet 114 so as to flow down hollow shaft 98 along arrow A. Upon reaching the entrance to vessel 60, the mixed liquid enters one of the flow channels 218 (Figure 9) and proceeds to fill vessel 60. As a result of the centrifugal force produced by the rotation of vessel 60 and the impact of the mixed liquid against minor disk 234, the mixed liquid is pushed radially outwardly towards wall 92 of vessel 60 and around disk 234.

[00105] The mixed liquid includes a heavy component 241 and a light component 243 which are defined by their relative densities. It is appreciated that heavy component 241 may also include comprise particulate matter. Where the mixed liquid includes more than two immiscible liquids, heavy component 241 or light component 243 can be defined to include more than one liquid. The drawn off liquid that includes more than one liquid can subsequently be processed through a second liquid-liquid separator 244 so as to separate the liquids therein.

[00106] As a result of the applied centrifugal force, heavy component 241 flows toward wall 92 at equator 97. Light component 243 flows toward the center or rotational axis 90 of vessel 60. As a result, a boundary line 245 is formed between heavy component 241 and light component 243. Boundary line 245 is maintained within a range of radial distances away from rotational axis 90. This liquid-liquid boundary line 245 is analogous to boundary line 228 depicted in Figure 10 for solid-liquid separator 10. In contrast, however, liquid-liquid boundary line 245 is typically positioned at a radial distance from rotational axis 90 in a range from about 1/5 to about 4/5 the distance between rotational axis 90 and the maximum diameter at equator 97,



Order	Item	Quantity	Unit Price	Total Price
1	1000	1000	1000	1000000
2	2000	2000	2000	4000000
3	3000	3000	3000	9000000
4	4000	4000	4000	16000000
5	5000	5000	5000	25000000
6	6000	6000	6000	36000000
7	7000	7000	7000	49000000
8	8000	8000	8000	64000000
9	9000	9000	9000	81000000
10	10000	10000	10000	100000000

**WORKMAN, NYDEGGER & SEELEY**  
A PROFESSIONAL CORPORATION  
ATTORNEYS AT LAW  
1000 EAGLE GATE TOWER  
60 EAST SOUTH TEMPLE  
SALT LAKE CITY, UTAH 84111

**WORKMAN, NYDEGGER & SEELEY**  
A PROFESSIONAL CORPORATION  
ATTORNEYS AT LAW  
1000 EAGLE GATE TOWER  
60 EAST SOUTH TEMPLE  
SALT LAKE CITY, UTAH 84111

**WORKMAN, NYDEGGER & SEELEY**  
A PROFESSIONAL CORPORATION  
ATTORNEYS AT LAW  
1000 EAGLE GATE TOWER  
60 EAST SOUTH TEMPLE  
SALT LAKE CITY, UTAH 84111

and light component 243 as discussed above. Control system 290 includes a first valve 248 coupled with effluent line 78 and a second valve 256 coupled with removal line 76.

[00110] According to the present invention, a pressure differential is maintained between first valve 248 and second valve 256. The pressure differential is needed to maintain boundary line 245 at a defined radial distance from rotational axis 90 such that only light component 243 exits through effluent channel 132 and effluent line 78 and only heavy component 241 exits through extraction tubes 160, exit tube 128, and removal line 76. Failure to establish and maintain a pressure differential between valves 248 and 256 can result in boundary line 245 extending beyond extraction tubes 160 such that a portion of light component 243 exits with heavy component 241 through extraction tubes 160 or can result in boundary line extending into effluent channel 132 such that a portion of heavy component 241 exits with light component 243 through effluent channel 132.

[00111] The pressure differential is based on the operating properties of separator 244, such as rotational velocity, and the material properties of supply stream 30, such as the density and viscosity of the at least two immiscible liquids contained within supply stream 30. The pressure differential is also based on the desired location of boundary line 245 within vessel 60. It is appreciated that in some embodiments the pressure differential can be zero or substantially zero so as to maintain boundary line 245 at the desired location.

[00112] In practice, the pressure differential can be empirically determined. For example, initially first valve 248 is set to operate at a first pressure. That is, first valve 248 maintains the exiting light component 243 at the first pressure while enabling exiting light component 243 to continually flow through first valve 248. Accordingly,

if the flow of exiting light component 243 decreases, first valve 248 automatically closes a corresponding amount so as to maintain the first pressure. In this regard, first valve 248 can comprises a back-pressure regulator such as a Fisher 98L made by Fisher Controls International, Inc., out of Marshall Town, Iowa. Alternatively, first valve 248 can comprise a piloted or controlled back-pressure regulator, also available from by Fisher Controls International, Inc., which operates in communication with a pressure sensor 246 coupled effluent line 78. In either the above embodiments or other alternative valve configurations, first valve 248 is configured to automatically adjust so as to maintain a desired pressure on exiting light component 243 as the flow rate thereof changes. Where the flow rate is substantially constant, first valve 248 can be configured for manual rather than automatic adjustment.

[00113] The amount of first pressure is in some regards arbitrary since it is the pressure differential that controls the position of boundary line 245. In one embodiment, however, first pressure is typically in a range between about 1 psi ( $6.89 \times 10^3$  Pa) to about 600 psi ( $4.14 \times 10^6$  Pa) with about 30 psi ( $2.07 \times 10^5$  Pa) to about 125 psi ( $8.61 \times 10^5$  Pa) being more preferred. In other embodiments, the pressure can be greater or smaller.

[00114] Once the first pressure for first valve 248 is set, second valve 256 is initially set to operate at the same pressure. Liquid-liquid separator 244 is then operated at a flow rate for supply stream 30 and at a defined rotational velocity for vessel 60. The operating pressure for second valve 256 is then incrementally varied in opposite directions so as to determine the extreme operating pressures for second valve 256. For example, the operating pressure for second valve 256 can be incrementally decreased and then incrementally increased so as to determine the pressures for second valve 256

at which light component 243 first starts to flow out of removal line 76 with heavy component 241 and heavy component 241 first starts to flow out of effluent line 78 with light component 243.

[00115] Once the two extreme operating pressures for second valve 256 are determined, second valve 256 is set to operate at a pressure between the two extreme pressures. This places boundary line 245 substantially centrally between the opening to effluent channel 132 and opening 166 to extraction tubes 160. Alternatively, second valve 256 can be set to operate at any desired pressure between the two extreme pressures. The resulting pressure difference between first valve 248 and second valve 256 defines the pressure differential. Second valve 256 can comprise the same type of valves as discussed above with regard to first valve 248. As such, in one embodiment, second valve 256 can operate in conjunction with a pressure sensor 252 coupled with removal line 76.

[00116] One of the unique benefits of the inventive system is its ability to compensate for changes in the ratio of the two immiscible liquids in supply stream 30. For example, assuming an oil/water supply stream 30 feeds liquid-liquid separator 244 at a 50/50 mixture. At a given time, the 50/50 mixture suddenly experiences a load change to 10% oil and 90% water. Where the rotational velocity of liquid-liquid separator 244 remains substantially constant, an increased amount of water (heavy component 241) will tend to cause boundary line 245 to move toward rotational axis 90. Accordingly, the pressure sensed at first valve 248 will decrease while the pressure sensed at second valve 256 will increase. As a result, second valve 256 will automatically close slightly and first valve 248 will automatically open slightly. As a result, the operating pressures for valves 248 and 256 and the pressure differential

between valves 248 and 256 are continually held relatively constant even though the ratio of liquids in supply stream 30 may continually change. As such, the position of boundary line 245 is held relatively constant within vessel 60.

[00117] A 100% water supply stream 30 or a 100% oil supply stream 30 may also be controlled by maintaining boundary line 245 within the preferred distance range from rotational axis 90. For example, where a 100% oil supply stream 30 is fed to liquid-liquid separator 244, second valve 256 will eventually shut entirely in order to maintain the liquid-liquid interface within the preferred distance range away from rotational axis 90. Accordingly, where all liquid in supply stream 30 is oil, the oil will move through liquid-liquid separator 244 substantially without any mixing with the water that, under this situation, would be substantially stagnant therein.

[00118] Another embodiment of a control system 294 is depicted in Figure 13B. Like elements between control system 290 and 294 are depicted by like reference characters. In contrast to control system 290 where second valve 256 measures the pressure in removal line 76, in control system 294 pressure sensor 252 is coupled with effluent line 78. A signal line 254 couples sensor 252 to second valve 256. In this embodiment, second valve 256 is set to operate at a pressure differential relative to the set operating pressure of first valve 248. By way of example, where first valve 248 is set to operate at 20 psi, second valve 256 may be set to operate at a pressure of +5 psi relative to the sensed pressure in effluent line 78. Accordingly, although both valves 248 and 256 measure the pressure in effluent line 78, a predefined pressure differential is maintained between the two valves. Although sensors 246 and 252 are shown in Figure 13 as both being coupled with effluent line 78, in an alternative embodiment sensors 246 and 252 can each be coupled with removal line 76. In one embodiment

second valve 256 may be a differential pressure regulator such as a Fisher 98LD made by Fisher Controls International, Inc., out of Marshall Town, Iowa.

[00119] In yet another embodiment, it is appreciated that first valve 248 in control system 294 can be configured such that it does not adjust the pressure on effluent line 78 as the flow rate of fluid passing therethrough changes. For example, first valve 248 can be configured such that as the amount of exiting light component 243 passing therethrough decreases, the fluid pressure within effluent line 78 can also be allowed to decrease. However, since second valve 256 is set to operate at a pressure relative to the pressure of effluent line 78, the operating pressure of second valve 256 also decreases, thereby maintaining the desired pressure differential between valves 248 and 256.

[00120] In yet another embodiment depicted in Figure 13C, a controller 260 is used to withdraw the separated fluids from liquid-liquid separator 244. Signals are transmitted from first pressure sensor 246 by use of a first transmitter 262 that operates, by way of non-limiting example with a 4-20 mA signal. Similarly, first valve 248 transmits a signal by use of a first I/P converter 264 also with a 4-20 mA signal. First I/P converter 264 converts a 4-20 mA control signal to a pneumatic signal in order to operate first valve 248. Removal line 76 is also configured with second pressure sensor 252, a second transmitter 266, a second valve 256, and a second I/P converter 268.

[00121] According to the present invention, when a load disturbance occurs within supply stream 30, first pressure sensor 246 and second pressure sensor 252 detect a change in respective pressures between exiting heavy component 241 passing through removal line 76 and exiting light component 243 passing through effluent line 78. According to the present invention, such a load disturbance will be noted by controller 260 and respective valves 248 and 256 will be adjusted in order to maintain boundary

line 245 at a preferred distance range away from rotational axis 90. According to this embodiment of the present invention, the pressure differential is maintained by the control of first valve 248 and second valve 256. Accordingly, the location of boundary line 245 may be maintained within the preferred distance range away from rotational axis 90.

[00122] In another configuration for operation, the embodiments depicted in Figures 13A, 13B and 13C can be mixed. For example, an alternative system could provide first valve 248 on effluent line 78 as discussed above with regard to Figure 13A and second valve 256 on removal line 76 as discussed with regard to Figure 13C. Second valve 256 would be coupled with the sensor, controller and other electronics as also discussed with regard to Figure 13C.

[00123] Depicted in Figure 14 is a control system 295 that operates in a slightly different way. Control system 295 includes a valve 296 coupled with effluent line 78. Valve 296 comprises a ball valve or other type of valve which can be fixed to produce a constant defined opening so that under normal operating procedures exiting light component 243 is under a first pressure. As the flow rate changes, however, it is not necessary for valve 296 to adjust to maintain the pressure.

[00124] Control system 295 also includes a valve 297, such as a solenoid valve, that is designed to selectively fully open and fully close. Valve 297 is electrically coupled with a sensor 298 that can be coupled with removal line 76 or effluent line 78. Valve 297 is set to fully open and close over a pressure range. For example, during one mode of operation valve 296 is always left open a defined amount while valve 297 is initially closed. When the pressure sensed by sensor 298 reaches a defined upper limit, as a result of the heavy component collecting within vessel 60, valve 297 is opened allowing

the heavy component to exit therethrough. Valve 297 remains open until the pressure sensed by sensor 298 drops to a lower limit at which time valve 297 is closed and the process is repeated. By controlling valve 297 over a narrow pressure range, boundary line 245 remains relatively constant. In alternative embodiments, it is appreciated that valves 296 and 297 can be switched between lines 76 and 78. Furthermore, valve 297 can be set to open and close over a defined time range and/or pressure range.

[00125] One feature of one embodiment of the present invention relating to control of the liquid-liquid separation system is the ability to separate immiscible liquids that have a specific gravity difference of less than about 5% of each other. The present invention is useful for separating immiscible liquids that have a specific gravity difference in a range from about 5% to about 0.5%, more preferably from about 4% to about 0.5%, and most preferably from about 3% to about 0.5%. Of course, the present invention is useful for separating immiscible liquids that have a specific gravity difference greater than 5%. Where a given liquid-liquid system is provided such that the specific gravities of the two liquids are known, control of such systems is achieved by the present invention. Calibration may be conducted for a given rotating pressurized vessel as disclosed herein. A first rpm may be established and various pressure differences noted for different ratios of the two liquids. A curve may be fitted to these data. Similarly, other rpm amounts may be tested in order to calibrate the rotating pressure vessel. By use of standard control methods such as a PID controller, the rpm amount of the rotating pressure vessel may be tracked and the liquid-liquid system separated by maintaining the boundary layer 245 within a desired range.

[00126] One application of liquid-liquid separator 244 is depicted in Figure 15. Under certain conditions, environmental discharge regulations may require water to be



cleaned of its entrained oil to a level below about 100 ppm. According to the embodiment of the present invention depicted in Figure 15, feed stream 12 comprises substantially no loose particulate material except for any incidental trash that may be removed in trash strainer 18. Supply stream 30 enters liquid-liquid separator 244 and the two immiscible liquids are separated as described above.

[00127] An exiting heavy component stream 250, which can comprise water in an oil/water system, is feed to a liquid-liquid hydrocyclone 270. Hydrocyclone 270 accomplishes a separation therein that removes more of the light component liquid from a concentration above about 100 ppm down to a concentration of less than about 10 ppm.

[00128] For example, where an oil/water system is provided, exiting heavy component stream 250 comprising the water may have an oil content of about 100 ppm. Liquid-liquid hydrocyclone 270 provides a purified heavy component liquid stream 272 that has an oil content in a range from about 0.1 to about 100 ppm, preferably from about 1 to about 10 ppm, and more preferably from about 2 to about 5 ppm. A recycle light component liquid stream 274 is drawn off liquid-liquid hydrocyclone 276 and is blended with flow path 20 to form supply stream 30. Typically, in a 50/50 oil/water flow path 20, the content of water within recycle light component liquid stream 274 will be in a range from about 50% water to about 80% water. Hydrocyclone 276 can comprise any hydrocyclone known to those skilled in the art. One example of a hydrocyclone is disclosed in United States Patent No. 5,133,861.

[00129] Accordingly, a method of separating a liquid-liquid mixture by use of separator 244 depicted in Figure 11 may include one of the control systems depicted in

Figures 13 and 14 or combination thereof and may additionally include a hydrocyclone that is connected to the heavy component outlet.

[00130] Another embodiment of the present invention is depicted in Figure 16, wherein the more expensive sphere pressure vessel 60 has been replaced with a double truncated cone pressure vessel 276. Figure 16 depicts extraction tubes 160 that are longer than their equivalents depicted in Figure 3. Additionally, a flanged edge 278 of the double truncated cone 276 is provided with a bolt 280 in order to assemble double truncated cone 276. A gasket or an o-ring (not pictured) may be placed between mating surfaces of flanged edge 278 in order to achieve a liquid-tight seal that holds under the pressure contemplated for the present invention.

[00131] Figure 16 also depicts the axial flow passage 174 to be more angular due to the shape of double truncated cone 276. One distinction of double truncated cone 276 is the absence of a decreasing flow slope. In other words, the flow slope along vessel wall 92 is constant for solid particulate matter or a heavy component liquid as it moves along vessel wall 92 in the direction toward radial extraction tube opening 166.

[00132] Figure 17 is a perspective view of a separator subassembly 292 including additional disks 202, 204 along with at least one major disk such as center disk 170. Figure 17 depicts a fin shape for radial fins 184 that conform with the double truncated cone shape of pressure vessel 276. An additional distinction between subassembly 292 and corresponding components in solid-liquid separator 10 is that an extraction tube 160 is disposed between each fin 184 in subassembly 292. In this embodiment, underflow passage 190 need not be formed between adjacent flow channels 218. According to the present invention, double truncated cone 270 depicted in Figures 16 and 17 may be used with either a solid-liquid separator or a liquid-liquid separator.

[00133] In yet another embodiment, it is envisioned that a single separator can be configured to simultaneously separate both two or more immiscible liquids and particulate matter from a fluid stream. The separator can be configured substantially identical to those disclosed in Figures 10 and 11. In this embodiment, however, the particulate matter collects at the farthest radial distance from the rotational axis, the lighter of the two immiscible liquids collects about the rotational axis, and the heavier of the two immiscible liquids collects between the particulate matter and the lighter liquid. Two separate sets of extractions tubes are used. The first set extends down to the particulate matter for extraction thereof. This is similar to that previously discussed with regard to Figure 10. The second set of extraction tubes extends to the heavier liquid for extraction thereof. The lighter liquid exits in the same manner as previously discussed with regard to Figure 11.

[00134] Depicted in Figure 18 is another alternative embodiment of a separator 300 which can function as a solid-liquid separator and/or a liquid-liquid separator. Separator 300 comprises a frame assembly 302 which includes a horizontally disposed base plate 304 and a spaced apart head plate 306 in substantially parallel alignment therewith. A cylindrical guard 308 extends between base plate 304 and head plate 306 so as to bound a compartment 310. Base plate 304 is supported by a plurality of adjustable legs 312 downwardly projecting therefrom.

[00135] Attached to and extending below base plate 304 is a stationary inlet housing 314. As discussed below in greater detail, a fluid inlet line 311 and a fluid delivery line 313 are each fluid coupled with inlet housing 314. Fluid inlet line 311 is used to deliver the fluid that is to be separated, clarified, and/or otherwise treated. Accordingly, depending on the configuration and intended use of separator 300, fluid inlet line 311

[illegible]

**WORKMAN, NYDEGGER & SEELEY**  
A PROFESSIONAL CORPORATION  
ATTORNEYS AT LAW  
1000 EAGLE GATE TOWER  
60 EAST SOUTH TEMPLE  
SALT LAKE CITY, UTAH 84111

**[00138]** A shaft assembly 322, which is also configured to rotate about rotational axis 466, extends through and is rigidly coupled with pressure vessel 316. Shaft assembly 322 includes an inlet end 324 that is rotatably supported within inlet housing

314. Shaft assembly 322 also includes an outlet end 326 that is rotatably supported within outlet housing 315.

[00139] Encircling shaft assembly 322 and attached to pressure vessel 316 at inlet end 318 is an annular pulley 328. Returning to Figure 18, a motor 330 is mounted to base plate 304. Motor 330 rotates a drive wheel 332 which is also disposed within compartment 310. A belt 334 extends between drive wheel 332 and pulley 328 so as to facilitate rotation of pressure vessel 316 and shaft assembly 322 relative to stationary inlet housing 314 and stationary outlet housing 315. In this regard, it is appreciated that bearings are disposed between shaft assembly 322 and housings 314 and 315.

[00140] Depicted in Figure 20, shaft assembly 322 comprises a central manifold 336. As depicted in Figure 22, manifold 336 comprises a substantially cylindrical collar 337 having an interior surface 338 that extends between an inlet end 340 and an opposing outlet end 342. Radially inwardly projecting from interior surface 338 of collar 337 is an annular flange 344. Flange 344 circles a compartment 339. A plurality of radially spaced apart channels 346 extend through manifold 336 and flange 344 at the outlet side of flange 344. Each channel 346 comprises a first channel portion 341, a second channel portion 343, and a third channel portion 345, each portion being concentrically disposed and consecutively constricting toward compartment 339.

[00141] An end wall 353 extends across flange 344 on the outlet side of channels 346 so as to bound one side of compartment 339. An annular mouth 355 projects from end wall 353 and flange 344 toward outlet end 342. Extending between mouth 355 and collar 337 so as to communicate with second channel portion 343 of each channel 346 is an annular slot 357.

[00142] Returning to Figure 20, shaft assembly 322 also includes a tubular input shaft 350. Input shaft 350 extends from a first end 352, which corresponds to inlet end 324 of shaft assembly 322, to an opposing second end 354. Second end 354 is securely disposed within inlet end 340 of manifold 336 so as to bias against flange 344. Input shaft 356 has an interior surface 360 that bounds a fluid delivery channel 362. Delivery channel 362 extends from an inlet mouth 364 at first end 352 to channels 346 of manifold 336. As depicted in Figure 19, inlet mouth 364 is in sealed fluid communication with a coupling port 365 formed on inlet housing 314. In turn, coupling port 365 is fluid coupled with fluid delivery line 313 as previously discussed with regard to Figure 18. As such, fluid entering through delivery line 313 passes through inlet housing 314 and into fluid delivery channel 362.

[00143] Returning to Figure 20, input shaft 350 comprises a tubular inner shaft 356 and a tubular outer shaft 358 encircling inner shaft 356. Inner shaft 356 and outer shaft 358 each extend between first end 352 and second end 354. A plurality of radially spaced apart inlet ports 366 extend through outer shaft 358 at or toward first end 352. Similarly, a plurality of radially spaced apart outlet ports 368 extend through outer shaft 358 at or toward second end 354. An extension tube 370 is coupled with and radially outwardly projects from each outlet port 368. Formed between inner shaft 356 and outer shaft 358 and longitudinally running from inlet ports 366 to outlet ports 368 is a substantially cylindrical fluid inlet channel 372.

[00144] As depicted in Figure 19, outlet ports 368 and extension tubes 370 are disposed within pressure vessel 316. In contrast, inlet ports 366 are in sealed fluid communication with a coupling port 373 formed on inlet housing 314. More specifically, as depicted in Figure 21, inlet housing 314 bounds a cavity 374 that

2025 FEB 10 09:00 AM

WORKMAN, NYDEGGER & SEELEY  
A PROFESSIONAL CORPORATION  
ATTORNEYS AT LAW  
1000 EAGLE GATE TOWER  
60 EAST SOUTH TEMPLE  
SALT LAKE CITY, UTAH 84111

encircles input shaft 350 at inlet ports 366. As such, cavity 374 is in fluid communication with inlet ports 366. Cavity 374 has an interior sidewall 375 that spirals so as to radially constrict.

[00145] Coupling port 373 extends into inlet housing 314 and connects with cavity 374 at an orientation tangential to cavity 374. In turn, fluid inlet line 311, as previously discussed with regard to Figure 18, is coupled with coupling port 373. Accordingly, as fluid enters through fluid inlet line 311, the fluid passes through cavity 374 and inlet ports 366 so as to enter fluid inlet channel 372. As a result of the tangential orientation of coupling port 373 and the spiral configuration of cavity 374, the fluid entering cavity 374 is forced to rotate within annular cavity 374 about rotational axis 466 of shaft assembly 322. The fluid is rotating in the same direction that shaft assembly 322 rotates. Although not required, this introduction of the fluid in a rotating orientation minimizes turbulent flow of the fluid passing into separator 300, thereby maximizing operating efficiency.

[00146] Returning to Figure 20, similar to input shaft 350, shaft assembly 322 also includes a tubular output shaft 376. Output shaft 376 extends from a first end 378 to an opposing second end 380. Second end 380 corresponds to outlet end 326 of shaft assembly 322. First end 378 is securely disposed within outlet end 342 of manifold 336. Output shaft 376 has an interior surface 382 that bounds an effluent channel 384. Effluent channel 384 extends from a sealed end wall 386 (Figure 22) at first end 378 to an open exit mouth 388 at second end 380. Furthermore, a plurality of radially spaced apart transfer tubes 400 extend in sealed fluid communication from the exterior of shaft assembly 322 to effluent channel 384 at first end 378.

[00147] As depicted in Figure 19, transfer tubes 400 are disposed in open fluid communication within pressure vessel 316. In contrast, outlet mouth 388 is in sealed fluid communication with a coupling port 404 formed on outlet housing 315. In turn, coupling port 404 is fluid coupled with effluent line 348 as previously discussed with regard to Figure 18. As such, fluid entering effluent channel 384 through transfer tubes 400, exits through outlet housing 315 and effluent line 348.

[00148] Returning to Figure 20, output shaft 376 also comprises a tubular inner shaft 390 and a tubular outer shaft 392 encircling inner shaft 390. Inner shaft 390 and outer shaft 392 each extend between first end 378 and second end 380. First end 378 of inner shaft 390 is received within mouth 355 of manifold 336 so as to bias against end wall 353. An annular seal 359 extends between inner shaft 390 and mouth 355.

[00149] A plurality of radially spaced apart removal ports 394 extend through outer shaft 392 at or toward second end 380. Formed between inner shaft 390 and outer shaft 392 and longitudinally running from annular slot 357 formed on manifold 336 to removal ports 394 is an annular channel 395. Channel 395 and annular slot 357 combine to form a removal channel 396 that extends from each channel 346 on manifold 336 to removal ports 394.

[00150] As depicted in Figure 19, removal ports 394 are in sealed fluid communication with a coupling port 402 formed on outlet housing 315. In one embodiment, coupling port 402 communicates with removal ports 394 in substantially the same fashion that inlet ports 366 fluid couple with coupling port 373, as discussed above with regard to Figure 21, except that the fluid is flowing in the opposite direction. Coupling port 402 is fluid coupled to removal line 347, as discussed with regard to



Figure 18, such that fluid and/or particulate matter entering removal channel 396 exits through removal ports 394, coupling port 402 and removal line 347.

[00151] Depicted in Figure 20, an extraction tube 410 is fluid coupled with and radially outwardly projects from each channel 346 of manifold 336. As depicted in Figure 23, each extraction tube 410 comprises an outer tube 412 having an interior surface 414 extending between a first end 416 and an opposing second end 418. Disposed within outer tube 412 is an inner tube 420. Inner tube 420 has an exterior surface 422 and an interior surface 424 each extending between a first end 426 and an opposing second end 428. First end 426 of inner tube 420 projects past first end 416 of outer tube 412. Interior surface of 424 of inner tube 420 bounds a supply duct 430. A removal duct 432 is bound between interior surface 414 of outer tube 412 and exterior surface 422 of inner tube 420.

[00152] As depicted in Figure 22, first end 426 of inner tube 420 of each extraction tube 410 is secured in fluid communication within third channel portion 345 of a corresponding channel 346 of manifold 336. As such, supply duct 430 is in fluid communication with compartment 339 of manifold 336 and fluid delivery channel 362. Furthermore, first end 416 of outer tube 412 of each extraction tube 410 is secured in fluid communication within first channel portion 345 of a corresponding channel 346 of manifold 336. As such, each removal duct 432 is in fluid communication with second channel portion 343 of a corresponding channel portion 346 which in turn is in fluid communication with effluent channel 384 by way of annular slot 357 in manifold 336.

[00153] Returning to Figure 23, each extraction tube 410 also includes a nozzle 436. Nozzle 436 comprises a tubular stem 438 having an interior surface 440 and an exterior surface 442 each extending between a first end 444 and an opposing second end 446.

Radially outwardly projecting from second end 446 of stem 438 is an annular flange 448. Second end 428 of inner tube 420 is securely disposed within stem 438 while second end 418 of outer tube 412 is securely disposed about the exterior of stem 438. A plurality of radially spaced apart slots 445 extend through outer tube 412 at second end 418. Slots 445 are in substantially parallel alignment with the rotational axis of outer tube 412. As a result, at least a portion of each slot 445 forms a channel extending from the exterior to removal duct 432. In one embodiment, each slot 445 is oriented so as to tangentially intersect with removal duct 432.

[00154] An annular sidewall 450 forwardly projects from the outer edge of flange 448. In turn, an annular lip 452 forwardly projects from the terminal end of sidewall 450. Secured inside of annular lip 452 so as to bias against sidewall 450 is an end cap 454. In this configuration, a disk shaped compartment 456 is encircled by sidewall 448 and bounded between end cap 454 and flange 448. Compartment 456 is in fluid communication with supply duct 430.

[00155] Depicted in Figure 24, sidewall 450 and lip 452 share a common outer face 458. Outer face 458 comprises six flat faces 460 each having a notch 462 formed thereon. A flush port 464 linearly extends from each notch 462 to compartment 456 by passing through sidewall 450. Each flush port 464 is configured to intersect tangentially with interior surface 451 of sidewall 450. As a result, fluid exiting through flush ports 464 exits at a generally tangential orientation to a radial arc from the center of nozzle 436. This is in contrast to the fluid exiting radially from flush ports 464. In view of the forgoing, fluid traveling down supply duct 430 passes through compartment 456 and out through flush ports 464. The fluid can then enter removal duct 432 through slots 445.

[00156] As illustrated in Figure 22, nozzle 436 is disposed adjacent to or directly against the interior of wall 468 of pressure vessel 316 at equator 474. As will be discussed below in greater detail, nozzle 436 can be further spaced radially inward from wall 468 but in some embodiments such positioning may be less efficient in removing particulate matter.

[00157] As with pressure vessel 60, pressure vessel 316 is also configured with a plurality of fins and discs for channeling fluid through vessel 316. An annular first disc 478 encircles input shaft 350, and is secured, such as by pins, bolts, welding and the like, to inlet end 340 of manifold 336. Similarly, an annular second disc 480 encircles output shaft 376 and is secured to outlet end 342 of manifold 336. Each of discs 478 and 480 is positioned perpendicular to rotational axis 466.

[00158] Intersecting with discs 478 and 480 are a plurality of fins 482. As depicted in Figure 25, each fin 482 comprises a inside edge 484 that extends between a first end 486 and an opposing second end 488 and a remaining perimeter edge 490. Inside edge 484 is configured to complementary fit over manifold 336 and is configured to run in parallel alignment with rotational axis 466. Perimeter edge 490 is configured substantially complementary to interior surface 470 of pressure vessel 316.

[00159] As depicted in Figures 22 and 25, perimeter edge 490 comprises a first cut out portion 492 at first end 486. First cut out portion 492 is formed radially out from the terminal end of extension tubes 370. As a result, an annular inflow equalizing channel 494 circles shaft assembly 322 within chamber 472 and is partially bounded between first cutout portion 492 of each fin 482 and interior surface 470 of pressure vessel 316.

[00160] Perimeter edge 490 of each fin 480 also comprises a second cut out portion 496 at second end 488. Second cut out portion 496 is formed radially out from transfer tubes 400. As a result, an annular outflow equalizing channel 498 circles shaft assembly 322 within chamber 472 and is partially bounded by second cutout portion 496 of each fin 482, interior surface 470 of pressure vessel 316, and output shaft 376.

[00161] Extending from inside edge 484 of each fin 482 are a pair of spaced apart disc receive slots 500. Complementary radially spaced apart slots are also formed on the outside edge of discs 478 and 480 so, as depicted in Figure 26, fins 482 and discs 478, 480 can be interlocked together by coupling the slot. This is the same form of interlocking as previously discussed with regard to that fins and discs in Figure 5. Fins 482 are thus secured to shaft assembly 322 and extend in parallel alignment with rotational axis 466. Bounded between each adjacent pair of fins 482 and extending between inlet end 318 to outlet end 320 is a flow channel 502.

[00162] As further depicted in Figures 22 and 26, where separator 300 is primarily being used separate fluids of different densities, such as oil and water, discs 478 and 480 are formed with openings 504 that extend therethrough in alignment with each fluid channel 502. Openings 504 allow the fluid to flow through the discs as opposing to having to flow around them. In this embodiment, discs 478 and 480 primarily function as supports for fins 482.

[00163] Depending on its intended use, the operation of separator 300 is similar to the operation of separator 10 and separator 244 as previously discussed. As such, the operating parameters previously discussed with regard to separators 10 and 244 are also applicable to separator 300. Returning to Figure 18, during operation motor 330 is activated causing rotation of pressure vessel 316 about rotational axis 466. Shaft

assembly 322, extraction tubes 410, and fins 482 with associated discs rotate concurrently with pressure vessel 316. A feed stream 506 is feed into separator 300 through inlet line 311. Feed stream 506 is preferably pressurized, such as by pump 80 in Figure 2, so that feed stream 506 is maintained under a predefined pressure within pressure vessel 316 during operation of separator 300.

[00164] With discs 478 and 480 having openings 504 therein (Figure 26), separator 300 is configured to primarily operate as a liquid-liquid separator. As such, for purposes of illustration feed stream 506 comprises at least two immiscible liquids of different density. The two liquids are again referred to as heavy component 241 and light component 243. The operation of separator 300 will be discussed with regard to separating the two components. Although separating of the two components can also facilitate at least some removal of particulate matter from light component 243, a later embodiment will be discussed with regard to operating separator 300 has a solid-liquid separator for removing particulate matter.

[00165] As illustrated in Figure 19, feed stream 506 passes from inlet line 311 (Figure 18) into coupling port 373 of inlet housing 314. As previously discussed with regard to Figure 21, feed stream 506 is forced to spin within cavity 374 so as to at least being matching the rotation of feed stream 506 with the rotation of shaft assembly 322. Spinning feed stream 506 next passes through inlet ports 366 and into fluid inlet channel 372 of input shaft 350. Feed stream 506 exits inlet channel 372 through extension tubes 370, thereby entering chamber 472 of pressure vessel 316. Although not required, in one embodiment the feed stream is now rotating at substantially the same speed as pressure vessel 316. The use of extension tubes 370 which radially outwardly extend from shaft assembly 322 forces inlet steam 506 exiting therefrom to

be subject to at least a portion of the gravitational force produced by separator 300. In alternative embodiments, extension tubes 370 can be removed.

[00166] As depicted in Figure 22, upon entering pressure vessel 316 the centrifugal force imposed due to the rotation of pressure vessel 316 pushes the stream radially outwardly towards wall 468. As the stream enters pressure vessel 316, it enters one of the flow channels 502 (Figure 26) and proceeds to fill vessel 316. As previously discussed, flow channels 502 help to eliminate the Coriolis effect. Although an extension tube 370 can be provided for each discrete flow channel 502, inflow equalizing channel 494 allows fluid communication at the entrance of flow channels 502, thereby helping to ensure a common fluid level and flow rate through each flow channel 502. In alternative embodiments, inflow equalizing channel 494 can be eliminated.

[00167] As feed stream 506 travels within flow channels 502 toward transfer tubes 400, the stream is subjected to the tremendous centrifugal forces imposed on it due to the rotation of vessel 316. Thus, the more dense component of the stream flows radially outwardly while the less dense component flows radially inwardly toward rotational axis 466. A boundary line 508, disposed parallel to rotational axis 320, is thus formed within chamber 472 denoting the separation between heavy component 241 and light component 243.

[00168] Light component 243 continues to travel within flow channels 502 to transfer tubes 400. The formation of outflow equalizing channel 498 allows fluid communication between each stream of light component 243 leaving its corresponding flow channel 502, thereby helping to ensure a common inflow through each of transfer tubes 400. As a result, there can be fewer transfer tubes 400 than flow channels 502.

Alternatively, a transfer tube 400 can be provided for each flow channel 502, thereby eliminating the need for outflow equalizing channel 498.

[00169] Returning to Figure 19, light component 243 enters effluent channel 384 through transfer tubes 400. Lighter component 243 subsequently exits effluent channel 384 and separator 300 through effluent line 348 (Figure 18) as either a final product or for subsequent processing.

[00170] Returning back to Figure 22, heavy component 241 is removed from vessel 316 by being drawn into removal duct 432 of each extraction tube 410 through slots 445 at the end thereof. In this regard, slots 445 can be positioned at any location radially out from boundary line 508. Heavy component 241 travels radially inward along removal ducts 432 where it subsequently passes through second channel portion 343 and into removal channel 396 by way of annular slot 357. In turn, heavy component 241 exits removal channel 396 and separator 300 by way of removal ports 394 and removal line 347. The removal of heavy component 241 and light component 243 is controlled using one of the control systems and methods as previously discussed with regard to Figures 13-14 so that boundary line 508 is maintained at a desired location or within a desired range within vessel 316.

[00171] In one embodiment, it is appreciated that an extraction tube 410 can be provided for each flow channel 502. In an alternative embodiment, an extraction tube 410 can be provided in every other flow channel 502 or in any other desired placement. Where an extraction tube 410 is not provided in each channel 502, some form of opening or gap is provided at the separating fin so that fluid communication of the heavy component 241 is provided between two or more flow channels 502. Such openings or gaps can be formed by underflow passage 190 as previously discussed.

[00172] It is appreciated that most fluids for which separation of the components is desired will also include some form of particulate matter. The particulate matter which is initially suspended within feed stream 506 enters flow channels 502 where under the gravitational force produced by separator 300 is forced to the interior of wall 468 primarily about equator 474. Periodically the collected particulate matter is removed from vessel to prevent an overbuild up within vessel 316.

[00173] By way of example, at periodic intervals valves 317 and 351 on fluid inlet line 311 and effluent line 348, respectively, are closed. Subsequently, valves 319 and 349 on delivery line 313 and removal line 347, respectively, are opened. Next, with vessel 316 still rotating, a cleaning stream 510 is pumped into delivery line 313. Cleaning stream 510 travels down delivery channel 362 where is subsequently passes into supply duct 430 of each extraction tube 410. Finally, cleaning stream 510 passes through flush ports 464 into chamber 472 of pressure vessel 316. As a result of the orientation of flush ports 464, the exiting cleaning stream 510 produces a swirling vortex around nozzle 436. The swirling vortex resuspends the particulate matter that has caked or otherwise deposited against the interior of wall 468. Simultaneously with delivering cleaning stream 510 into chamber 472, heavier component 241 now having the particulate matter suspended therein is drawn out through removal ducts 432 in extraction tubes 410 as previously discussed.

[00174] Once a desired amount particulate matter and heavy component 241 is removed, valves 319 and 349 on delivery line 313 and removal line 347, respectively, are closed. Valves 317 and 351 on fluid inlet line 311 and effluent line 348, respectively, continue to remain closed for a sufficient period of time to enable the resuspended solids to again settle against the interior of wall 468 as a result of the



rotation of pressure vessel 316. Although not required, this act helps to ensure that resuspended solids are not dawn out with the lighter component. Once the solids have again settled, valves 317 and 351 are opened and the process is continued. In yet another method of operation, it is appreciated that feed stream 506 and cleaning stream 510 can feed simultaneously for concurrently removing both the heavier component and the lighter component.

[00175] In alternative embodiments, it is appreciated that extraction tube 410 can have a variety of different configurations. For example, flush ports 464 can be positioned at any orientation including radially outward. Furthermore, flush ports 464 can be positioned to exit through end cap 454. Any of a number of other configurations for nozzle 436 in which fluid can be ejected therefrom for resuspension of the particulate matter can also be used.

[00176] In yet another embodiment as depicted in Figure 27, an extraction tube 514 is shown without the use of nozzle 436. Extraction tube 514 has an inner tube 516 bounding a supply duct 518 and a surrounding outer tube 520. A removal duct 522 is bound between inner tube 516 and outer tube 520. Each of tubes 516 and 518 extends between a first end 524 and an opposing second end 526. First end 524 of extraction tube 514 is coupled with manifold 316 in substantially the same way as extraction tube 410.

[00177] Second end 526 of each of tubes 516 and 520 are openly exposed as opposed to being coupled with nozzle 436. As such, fluid simply exits through supply duct 518 at second end 526 to resuspend the solids settled against pressure vessel 316 while the heavier component with the resuspended solids therein enters into removal duct 522 at second end 526. In this embodiment, outer tube 520 can be formed without slots 445.

If desired, however, a support collar (not shown) having holes extending therethrough can be positioned between inner tube 516 and outer tube 520 to maintain spacing between the tubes. It is also appreciated that the system can be manipulated so that cleaning stream 510 flows out of removal duct 522 into pressure vessel 316 while the heavy component 241 with the resuspended particulate matter is removed through supply duct 518.

[00178] Depicted in Figure 28 is another embodiment of an extraction tube 530. Extraction tube 530 comprises an integral tube 532 that bounds a supply duct 534 and an adjacently disposed removal duct 536. It is appreciated that one skilled in the art based on the teaching herein could modify manifold 336 to couple with a first end of extraction tube 530 so that supply duct 534 communicates with delivery channel 362 and removal duct 536 communicates with removal channel 396. Alternatively extraction tube 530 can also comprise two separate tubes, one that bounds supply duct 534 and one that bounds removal duct 536.

[00179] Further alternative embodiments of extraction tubes are disclosed in United States Patent No. 5,853,266, entitled Fluidising Apparatus which drawings thereof and disclosure set forth in the Detailed Description of the Invention are incorporated herein by specific reference. Various forms of extraction tubes can also be obtained from Merpro Limited out of Nailsea, Bristol, United Kingdom.

[00180] Although the above described embodiment of separator 300 can be used for the removal of some particulate matter, the configuration is primarily designed for separation of mixed liquids, *i.e.*, separating oil and water. As previously discussed, however, separator 300 can also function primarily as a solid-liquid separator. Under this embodiment it is desirable to maximize the application of the centrifugal force on

WORKMAN, NYDEGGER & SEELEY  
A PROFESSIONAL CORPORATION  
ATTORNEYS AT LAW  
1000 EAGLE GATE TOWER  
60 EAST SOUTH TEMPLE  
SALT LAKE CITY, UTAH 84111

the particulate matter within the fluid. Accordingly, depicted in Figure 29, a fin assembly is shown wherein each of the fins 482 interlock with a first disc 538 and a second disc 540 in substantially the same way that discs 478 and 480 interlocked with fins 482 in Figure 25. One distinction between discs 538, 540 and discs 478, 480 is that discs 538, 540 do not have large openings 504 extending therethrough. In one embodiment, however, one or more small gas ports 542 do extend through each of discs 538 and 540 adjacent to their inside perimeter edge.

[00181] Turning to Figure 22, assuming that discs 478 and 480 were replaced with discs 538 and 540, respectively, the fluid entering chamber 472 of pressure vessel 316 through extension tubes 370 is forced to initially travel around the outer perimeter of disc 538. In so doing, the fluid and particulate matter therein are subject to a greater centrifugal force than if they had simply passed through openings 504. The increased centrifugal force results in a higher concentration of the particulate matter settling against interior surface 470 of pressure vessel 316 primarily about equator 474. The clarified liquid is removed from pressure vessel 316 through transfer tubes 400 as previously discussed while the solids are periodically resuspended and removed through extraction tube 410 or the alternatives discussed therewith as also previously discussed. In one embodiment separator 300 can be operated using the method and valve assembly as discussed with regard to solid-liquid separator 10.

[00182] Any gas which enters vessel 316 passes through gas ports 542 and exits with the clarified liquid. Alternatively, the gas can be removed from the feed stream before it enters the separator by passing the stream through a commercially available needle valve or other device designed to remove gases from fluid streams. In this embodiment, gas ports 542 are not required.

[00183] One of the benefits of having disc 540 solid, thereby requiring all of the fluid to pass around the outer perimeter thereof, is that it extends the retention time of the fluid within pressure vessel 316. In general, the longer the retention time the more particulate matter is separated from the fluid. In alternative embodiments, however, first disc 538 can be solid while second disc 540 can have openings 540 formed therein.

[00184] The present invention may be embodied in other specific forms without departing from its spirit or essential characteristics. The described embodiments are to be considered in all respects only as illustrative and not restrictive. The scope of the invention is, therefore, indicated by the appended claims rather than by the foregoing description. All changes which come within the meaning and range of equivalency of the claims are to be embraced within their scope.

WORKMAN, NYDEGGER & SEELEY  
A PROFESSIONAL CORPORATION  
ATTORNEYS AT LAW  
1000 EAGLE GATE TOWER  
60 EAST SOUTH TEMPLE  
SALT LAKE CITY, UTAH 84111